

AGCO V-TRANS PLUS

SAE 10W-40 SUPER HIGH PERFORMANCE MULTI-FUNCTIONAL LOW FRICTION TRANSMISSION / HYDRAULIC OIL

AGCO V-Trans Plus 10W-40 is a super high performance multi-functional low-friction transmission / hydraulic oil. Designed as the premium choice for your tractor fleet, its superior formulation ensures optimum performance, reliability and longevity of your transmission and hydraulic components. Other applications include manual transmissions, hydraulic aggregates and final drives with or without wet brakes, and multi plate differentials.

Applications

AGCO approved for use in the following applications:

- Massey Ferguson Tractors – Transmission and Hydraulic reservoirs where Dyna-4, Dyna-6 , Dyna-VT and earlier transmissions are fitted.
- Fendt Tractors – Vario Transmissions.
- Suitable for use as an Engine Oil in Pre-1998 Tier 2 Diesel Engines.

Suitable for a large range of other machinery brands and applications including:

- Agricultural Machinery
- Construction Machinery
- Mining Machinery

Benefits and Advantages

- Superior variable temperature viscosity behaviour.
- Miscible with other engine or gear oils of same specification.
- Superior protection and performance ensures longevity and reliability.
- Rapid oil circulation.
- Rapid lubrication of all major components.

Specifications

Recommended for use where the following specifications are required:

- SAE J300: 10W-40
- API GL-4
- API CG-4
- DEUTZ DQC I-02
- FENDT KDM 41.2011
- ZF TE-ML 06B, 06F, 07B



Blended in Australia.

Recommendations

Recommended for use where the following specifications and approvals are required:

- Massey Ferguson CMS M 1145
- SAE J306: SAE 75W-90
- DIN 51524-3: HVLP
- API GL5 in Tractors (without HOLMER)
- AFNOR NFE 48603 HV, ALLISON C-4
- CASE MS 1207, 1209, 1210, 1230,
- CNH MAT 3505, 3509, 3525, 3526
- FORD M2C134-D, M2C159 B/C
- John Deere JDM J 20 C
- New Holland 82009201/2/3
- ZF TE-ML 06A, 06C, 06L

Typical Characteristics

Density at 15 °C	DIN 51757	0.878 g/ml
Colour	DIN ISO 2049	4.5 ASTM
Flash Point, CoC	DIN ISO 2592	220 °C
Pour Point	DIN ISO 3016	-33 °C
Kinematic Viscosity at 40°C	DIN 51562-1	93.3 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	14.4 mm ² /s
Viscosity Index	DIN ISO 2909	160

Remember to always follow the manufacturers lubrication specification guidelines.

For more product safety information refer to the latest Safety Data Sheet available from AGCO Australia Limited Parts Customer Service Team. Avoid release into the environment. Dispose of container and contents according to all Federal and State Laws and Regulations.